

SIZE A4

PPOJECTION ◆

www.morethanall.com

MATERIALS:

- (1) HOUSING: HI-TEMP.PLASTIC(94V-0)
- (2) CONTACT:

 COPPER ALLOY(t=0.2mm)
 PLATING GOLD OVER NICKEL
 SPECIFICATION:
 - (1) CURRENT RATING: 0.5A MAX
 - (2) INSULATION RESISTANCE: 1000 M MINAT 500V DC.
 - (3) DIELECTRIC WITHSTANDING VOLTAGE: 150V(r.m.s) AC AT 0.5mA FOR 1 MINUTE
 - $(4) \quad CONTACRESISTANC \\ \textbf{50m} \quad MAX.$
 - (5) OPERATING TEMPERATURE: -40°C~+105°C
 - (6) MAX. PROCESSING TEMP: 230°C FOR 30 ~ 60 SECONDS

6.00 6.50 7.00 7.50 8.00 9.00 9.50 10.00 11.50 11.50 12.00 12.50 13.00 14.50 14.50	3.95 4.45 5.45 5.95 6.45 6.95 7.45 8.95 8.95 9.45 9.95 10.45 10.95 11.95	2.50 3.00 3.50 4.00 5.00 5.50 6.00 6.50 7.00 8.50 9.00 9.50
6.50 7.00 7.50 8.00 8.50 9.00 9.50 10.00 11.00 11.50 12.00 12.50 13.00 14.50 14.50 15.00	4.45 4.95 5.45 5.95 6.45 7.45 7.95 8.95 9.45 9.95 10.45 10.95 11.45	3.00 3.50 4.00 4.50 5.00 6.50 7.00 7.50 8.00 8.50 9.00 9.50
7.50 8.00 8.50 9.00 9.50 10.00 11.50 11.50 12.50 13.50 14.00 14.50 15.00	5.45 5.95 6.45 6.95 7.45 7.95 8.95 9.45 9.95 10.45 10.95 11.45	3.50 4.00 4.50 5.00 5.50 6.00 6.50 7.00 7.50 8.00 8.50 9.00 9.50
8.00 8.50 9.00 9.50 10.00 10.50 11.50 12.00 12.50 13.50 14.00 14.50 15.00	5.95 6.45 6.95 7.45 7.95 8.95 8.95 9.45 9.45 10.45 10.95 11.45	4.50 5.00 5.50 6.00 6.50 7.00 7.50 8.00 8.50 9.00 9.50 10.00
8.00 8.50 9.00 9.50 10.00 10.50 11.50 12.00 12.50 13.50 14.00 14.50 15.00	6.45 6.95 7.45 7.95 8.95 8.95 9.45 9.95 10.45 10.95 11.45	5.00 5.50 6.00 6.50 7.00 7.50 8.00 8.50 9.00 9.50 10.00
8.50 9.00 9.50 10.00 10.50 11.50 12.00 12.50 13.50 14.00 14.50 15.00	6.95 7.45 7.95 8.95 8.95 9.45 9.95 10.45 10.95 11.45	5.00 5.50 6.00 6.50 7.00 7.50 8.00 8.50 9.00 9.50 10.00
9.50 10.00 10.50 11.00 11.50 12.00 12.50 13.00 13.50 14.00 14.50	6.95 7.45 7.95 8.95 8.95 9.45 9.95 10.45 10.95 11.45	6.00 6.50 7.00 7.50 8.00 8.50 9.00 9.50 10.00
10.00 10.50 11.00 11.50 12.00 12.50 13.00 13.50 14.00 14.50 15.00	7.95 8.95 8.95 9.45 9.95 10.45 10.95 11.45	6.50 7.00 7.50 8.00 8.50 9.00 9.50 10.00
10.50 11.00 11.50 12.00 12.50 13.00 13.50 14.00 14.50 15.00	8.95 8.95 9.45 9.95 10.45 10.95 11.45 11.95	7.00 7.50 8.00 8.50 9.00 9.50 10.00
11.00 11.50 12.00 12.50 13.00 13.50 14.00 14.50 15.00	8.95 9.45 9.95 10.45 10.95 11.45 11.95	7.50 8.00 8.50 9.00 9.50 10.00
11.50 12.00 12.50 13.00 13.50 14.00 14.50 15.00	9.45 9.95 10.45 10.95 11.45 11.95	8.00 8.50 9.00 9.50 10.00
12.00 12.50 13.00 13.50 14.00 14.50	9.95 10.45 10.95 11.45 11.95	8.50 9.00 9.50 10.00
12.50 13.00 13.50 14.00 14.50 15.00	10.45 10.95 11.45 11.95	9.00 9.50 10.00
13.00 13.50 14.00 14.50 15.00	10.95 11.45 11.95	9.50 10.00
13.50 14.00 14.50 15.00	11.45 11.95	10.00
13.50 14.00 14.50 15.00	11.45 11.95	10.00
14.00 14.50 15.00	11.95	
15.00		1 10.50
15.00	12.45	11.00
	12.95	11.50
15.50	13.45	12.00
16.00	13.95	12.50
16.50	14.45	13.00
17.00	14.95	13.50
17.50	15.45	14.00
18.00	15.95	14.50
18.50	16.45	15.00
19.00	16.95	15.50
19.50	17.45	16.00
20.00	17.95	16.50
20.50	18.45	17.00
21.00	18.95	17.50
21.50	19.45	18.00
22.00	19.95	18.50
22.50	20.45	19.00
23.00	20.95	19.50
23.50	21.45	20.00
24.00	21.95	20.50
24.50	22.45	21.00
25.00	22.95	21.50
25.50	23.45	22.00
26.00		22.50
26.50	24.45 23.00	
27.00	24.95	23.50
96 27.00 98 27.50		24.00
28.00	25.95	24.50
	16.00 16.50 17.00 17.50 18.00 19.50 19.50 20.50 21.00 21.50 22.00 22.50 23.50 24.00 24.50 25.50 26.50 27.00 27.50	16.00 13.95 16.50 14.45 17.00 14.95 17.50 15.45 18.00 15.95 18.50 16.45 19.00 16.95 19.50 17.45 20.00 17.95 20.50 18.45 21.00 18.95 21.50 19.45 22.00 19.95 22.50 20.45 23.00 20.95 23.50 21.45 24.00 21.95 24.50 22.45 25.00 23.95 26.50 24.45 27.00 24.95 27.50 24.95 27.50 25.45

Dimension

В

5.50 3.45 2.00

Circuits

	Mated Heigh		PART NO.	Н
	1.5mm	MALE	NP0519-P05P-xxx	1.25
		FEMALE	NP0519-S10P-xxx	1.35
	2.0mm	MALE	NP0519-P05P-xxx	1.25
		FEMALE	NP0519-S15P-xxx	1.95
	2.5mm	MALE	NP0519-P10P-xxx	1.75
		FEMALE	NP0519-S15P-xxx	1.95
	3.0mm	MALE	NP0519-P05P-xxx	1.25
		FEMALE	NP0519-S25P-xxx	2.85

DESCRIPTION:

RoHS Compliant TOLE		TOLEDANICES ADE		ORDER INFORMATION
KOHS COMPHANT		TOLERANCES ARE	NP0519-SxxP-xxx-LF	
CORETHANALL PCB CONNECTORS Cable ASSEMBLIES 煜倫股份有限公司	DRAWING BY CY			SERIES T LEADFREE
	CHECKED BY GENIUS		昭日框	SERIES 010~100WAY
	UNIT/mm SCALE 1:1		八八八三	UNMATED HIGH
	DATE			FEMALE