

D-D

NOTE

A. Material:

1. Housing : Nylon-9T Halogen Free, UL94V-0, Black
2. Contact : Copper Alloy

B. Plating: Gold plating

C. Temperature: -55 to 125

D. Electrical:

1. Voltage : 50V.
2. Current : 0.5A.
3. Contact Resistance : 40m Ω max.
4. Dielectric Withstanding Voltage : 500V AC / 1 min.
5. Insulation Resistance : 100M Ω min.

Available Pins : 10~100 Contacts

PCB Layout For
Surface Mounting

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ± 0.25
.XX ± 0.10
.XXX ± 0.05
ANG ±

PPOJECTION



ORDER INFORMATION

NP08-S090P-xxx-HF
SERIES | | | HALOGEN FREE
| | | 010~100WAY
| | | POST
| | | UNMATED HIGH/ 0.95mm
| | | FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 0.80mm (0.031") Pitch Board To Board Male connector H = 3.55mm