



RECOMMENDED PCB LAYOUT (TOP VIEW)
(DIMENSION SHOWN IS FOR CONNECTOR WITH POSTS)

- NOTES:
- MATERIAL:
 - 1-1. HOUSING :GLASS-FILLED LCP UL 94 V-0
 - 1-2. CONTACTS:COPPER ALLOY
 - FINISH CONTACT:
 - 2-1. CONTACT AREA PLATING:HARD GOLD
 - 2-2. SOLDER AREA PLATING :TIN/LEAD
 - 2-3. BASE PLATING :NICKEL
 - RECOMMENDED PCB THICKNESS :1.0mm

120	59	35.4	37.0	38.8	41.05	42.6	40.2
100	49	29.4	31.0	32.8	35.05	36.6	34.2
80	39	23.4	25.0	26.8	29.05	30.6	28.2
60	29	17.4	19.0	20.8	23.05	24.6	22.2
50	24	14.4	16.0	17.8	20.05	21.6	19.2
40	19	11.4	13.0	14.8	17.05	18.6	16.2
30	14	8.4	10.0	11.8	14.05	15.6	13.2
20	9	5.4	7.0	8.8	11.05	12.6	10.2
Pos	N-1	DIMENSION					

MORETHANALL
CONNECTORS
ASSEMBLIES

煜倫有限公司

PART NO. NPH-S225-XXX		CHECKED BY CY		TOLERANCES ARE .X ± .XX ± .XXX ± AWG	DESCRIPTION: 0.6mm PITCH BORAD TO BOARD CONNECTOR, V/T, SMT RECEPTACLE
DWG NO. NPH-S225-XXX		DRAWING BY			
FILE NO.		PROJECTION		AREA	REVISIONS
UNIT / mm	SCALE 1:1			HK	DATE

