




Recommended P.C.B Layout

MATERIAL

Contact Pin : Brass

SPECIFICATION

- △ Current Rate : 8 AMP PER PIN(20AWG)
- Insulation Resistance : 5000MΩMin. at DC 500V
- Contact Resistance : 20mΩMax. at DC 100mA
- Dielectric Voltage : AC 500V for one minute
- △ Operation Temperature : -40°C to + 105°C

POLES	DIM E	POLES	DIM E
		26	31.75
2	1.27	27	33.02
3	2.54	28	34.29
4	3.81	29	35.56
5	5.08	30	36.83
6	6.35	31	38.10
7	7.62	32	39.37
8	8.89	33	40.64
9	10.16	34	41.91
10	11.43	35	43.18
11	12.70	36	44.45
12	13.97	37	45.72
13	15.24	38	46.99
14	16.51	39	48.26
15	17.78	40	49.53
16	19.05	41	50.80
17	20.32	42	52.07
18	21.59	43	53.35
19	22.86	44	54.61
20	24.13	45	55.88
21	25.40	46	57.15
22	26.67	47	58.42
23	27.94	48	59.69
24	29.21	49	60.96
25	30.48	50	62.23

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

X. ±
.X ± 0.30
.XX ± 0.20
.XXX ±
ANG ± 3°

照片框

ORDER INFORMATION

P-V38X32C-1XxxR-LF
SERIES T LEADFREE
R TYPE FOOT
180°SMT HIGH 3.8mm
CAP CONTACT 3.2mm
NON POST

DESCRIPTION: PIN HEADER 1.27*2.54mm
SMT S/T TYPE, SINGLE ROW CAP+TUBE