

Recommended P.C.B Layout

**MATERIAL**

Contact Pin : Brass

Insulator: NY6T UL94-V0 


**SPECIFICATION**

Current Rate : 1 AMP

Insulation Resistance : 5000MΩMin. at DC 500V

Contact Resistance : 20mΩMax. at DC 100mA

Dielectric Voltage : AC 500V for one minute

Operating Temperature: -40°C to +105°C 

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION 

X. ±  
.X ± 0.30  
.XX ± 0.20  
.XXX ±  
ANG ± 3°

照片框

**ORDER INFORMATION**

P-V38X48-2Xxx-LF  
SERIES | LEADFREE  
180°SMT | 2X02:04 WAY  
| 2X50:100 WAY  
| CONTACT 4.8mm  
| NON POST  
| HIGH 3.8mm

DESCRIPTION: PIN HEADER 1.27\*2.54mm SMT S/T TYPE, DUAL ROWS