

Recommended P.C.B Layout

**MATERIAL**

Insulator: NY6T UL94-V0  
 Contact Pin : Brass

**SPECIFICATION**

Current Rate : 1 AMP  
 Insulation Resistance : 5000MΩMin. at DC 500V  
 Contact Resistance : 20mΩMax. at DC 100mA  
 Dielectric Voltage : AC 500V for one minute  
 Operation Temperature : -40°C to + 105°C

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X, ±  
 .X ± 0.30  
 .XX ± 0.20  
 .XXX ±  
 ANG ± 3°



**ORDER INFORMATION**

P-V38X50-1X12R-LF  
 SERIES | CONTACT 5.0mm | HIGH 3.8mm  
 180°SMT | NON POST  
 LEADFREE R TYPE FOOT  
 12 WAY

DESCRIPTION: PIN HEADER 1.27\*2.54mm SMT S/T TYPE, SINGLE ROW TUBE