



**MATERIAL**


Insulator : NYLON 46  
Contact Pin : Brass

**SPECIFICATION**

Current Rate : 1 AMP  
Insulation Resistance : 5000MΩMin. at DC 500V  
Contact Resistance : 20mΩMax. at DC 100mA  
Dielectric Voltage : AC 500V for one minute  
Operation Temperature : -40°C to + 105°C



POLES	DIM E	POLES	DIM E
		26	31.75
2	1.27	27	33.02
3	2.54	28	34.29
4	3.81	29	35.56
5	5.08	30	36.83
6	6.35	31	38.10
7	7.62	32	39.37
8	8.89	33	40.64
9	10.16	34	41.91
10	11.43	35	43.18
11	12.70	36	44.45
12	13.97	37	45.72
13	15.24	38	46.99
14	16.51	39	48.26
15	17.78	40	49.53
16	19.05	41	50.80
17	20.32	42	52.07
18	21.59	43	53.34
19	22.86	44	54.61
20	24.13	45	55.88
21	25.40	46	57.15
22	26.67	47	58.42
23	27.94	48	59.69
24	29.21	49	60.96
25	30.48	50	62.23



Recommended P.C.B Layout

PA-R15-2Xxx-LF  
LEADFREE  
RoHS Compliant



PART NO. PA-R15-2Xxx

DWG NO. PA-R15-2Xxx

FILE NO.

APPROVED BY CY

DRAWING BY

TOLERANCES ARE  
.0 =±.30  
.00 =±.15  
.000 =±.XXX  
.0000=±.  
ANG.=±3°

DESCRIPTION:  
AREA

PIN HEADER 1.27\*1.27mm  
RIGHT ANGLE TYPE, DUAL ROWS

REVISIONS  
HK  
DATE

煜倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION

