



Recommended P.C.B Layout

MATERIAL

Contact Pin : Brass

SPECIFICATION

Current Rate : 1 AMP

Insulation Resistance : 5000MΩMin. at DC 500V

Contact Resistance : 20mΩMax. at DC 100mA

Dielectric Voltage : AC 500V for one minute

Operation Temperature : -40°C to + 105°C

POLES	DIM E	POLES	DIM E
2	1.27	26	31.75
3	2.54	27	33.02
4	3.81	28	34.29
5	5.08	29	35.56
6	6.35	30	36.83
7	7.62	31	38.10
8	8.89	32	39.37
9	10.16	33	40.64
10	11.43	34	41.91
11	12.70	35	43.18
12	13.97	36	44.45
13	15.24	37	45.72
14	16.51	38	46.99
15	17.78	39	48.26
16	19.05	40	49.53
17	20.32	41	50.80
18	21.59	42	52.07
19	22.86	43	53.34
20	24.13	44	54.61
21	25.40	45	55.88
22	26.67	46	57.15
23	27.94	47	58.42
24	29.21	48	59.69
25	30.48	49	60.96
		50	62.23

PA-R25xxyy-2Xxx-LF
LEADFREE
A 30:3.0mm B 23:2.3mm

RoHS Compliant



PART NO. PA-R25xxyy-2Xxx

DWG NO. PA-R25xxyy-2Xxx

FILE NO.

CHECKED BY CY

DRAWING BY

TOLERANCES ARE
.X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIPTION:

PIN HEADER 1.27*1.27mm
RIGHT ANGLE TYPE, DUAL ROWS

煜倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION

AREA

REVISIONS

HK

DATE