



Recommended P.C.B Layout

MATERIAL

△ Contact Pin : Brass  
 △ Insulator: NY6T UL94-V0

SPECIFICATION

Current Rate : 1 AMP  
 Insulation Resistance : 5000MΩMin. at DC 500V  
 Contact Resistance : 20mΩMax. at DC 100mA  
 Dielectric Voltage : AC 500V for one minute  
 △ Operating Temperature : -40°C to +105°C

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±  
 .X ± 0.30  
 .XX ± 0.20  
 .XXX ±  
 ANG ± 3°

P PROJECTION

照片框

ORDER INFORMATION

PA-V15X30C-2X10-LF  
 SERIES | | | | | LEADFREE  
 | | | | | 20 WAY  
 | | | | | CAP  
 | | | | | CONTACT 3.0mm  
 | | | | | NON POST  
 | | | | | HIGH 1.5mm  
 180°SMT

DESCRIPTION: PIN HEADER 1.27\*1.27mm SMT S/T TYPE, DUAL ROWS CAP+TAPE