



Recommended P.C.B Layout

MATERIAL

Insulator: NY46

Contact Pin : Brass

SPECIFICATION

Current Rate : 1 AMP

Insulation Resistance : 5000MΩMin. at DC 500V

Contact Resistance : 20mΩMax. at DC 100mA

Dielectric Voltage : AC 500V for one minute

POLES	DIM E	POLES	DIM E	POLES	DIM E
2	1.27	17	20.32	34	41.91
		18	21.59	35	43.18
		19	22.86	36	44.45
3	2.54	20	24.13	37	45.72
4	3.81	21	25.40	38	46.99
5	5.08	22	26.67	39	48.26
6	6.35	23	27.94	40	49.53
7	7.62	24	29.21	41	50.80
8	8.89	25	30.48	42	52.07
9	10.16	26	31.75	43	53.34
10	11.43	27	33.02	44	54.61
11	12.70	28	34.29	45	55.88
12	13.97	29	35.56	46	57.15
13	15.24	30	36.83	47	58.42
14	16.51	31	38.10	48	59.69
15	17.78	32	39.37	49	60.96
16	19.05	33	40.64	50	62.23

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ±
ANG ± 3°

照片框

ORDER INFORMATION

PA-V20X-1XxxL-LF
SERIES
180°SMT
HIGH 2.0mm
LEADFREE
L:L TYPE FOOT POSITION
1X02:02 WAY
1X50:50 WAY
NON POST

DESCRIPTION: PIN HEADER 1.27*1.27mm SMT S/T TYPE, SINGLE ROW