


A: 5.84 mm



P. C. B . LAYOUT

MATERIAL

HOUSING : NY6T, UL-94V0

CONTACT: COPPER ALLOYS

PLATED : GOLD FLASH

COLOR : BLACK

SPECIFICATION

CURRENT : 1A

OPERATING TEMPERAURE : -55° C TO +105° C

CONTACT RESISTANCE : 20 MILLIOHMS MAX

INSULATION RESISTANCE: 1000 MEGAOHMS MIN

WITHSTAND VOLTAGE : 500 V AC/minute

CONTACTS

	2×11	2×21	2×31
2×02	2×12	2×22	2×32
2×03	2×13	2×23	2×33
2×04	2×14	2×24	2×34
2×05	2×15	2×25	2×35
2×06	2×16	2×26	2×36
2×07	2×17	2×27	2×37
2×08	2×18	2×28	2×38
2×09	2×19	2×29	2×39
2×10	2×20	2×30	2×40

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.38
.XX ± 0.25
.XXX ±
ANG ± 5°

照片框

ORDER INFORMATION

PA-V30X30-2Xxx-LF
SERIES
180°SMT
LEADFREE
2X02:04 WAY
2X40:80 WAY
CONTACT 3.0mm
NON POST
HIGH 3.0mm

DESCRIPTION: 1.27PH SMT H:2.50 2*XXPIN