


PCB LAYOUT (BOTTOM VIEW)



| NO. | NAME | MATERIAL | FINISH | Q'TY |
|-----|------------|--------------------|---------------|------|
| 1 | BARREL | C.R.S T:0.50 | NICKEL PLATED | 1 |
| 2 | FRONT RING | PBT G.F. | WHITE | 1 |
| 3 | BACK RING | PBT G.F. | WHITE | 1 |
| 4 | FRAME | C.R.S T:0.50 | TIN PLATED | 1 |
| 5 | CENTER PIN | PHOS.BRONZE T:0.30 | TIN PLATED | 1 |
| 6 | CLIP | C.R.S T:0.50 | NICKEL PLATED | 1 |

Specification:

Contact Resistance: 50m Ohm Max.
 Insulation Resistance: 500M Ohm Min. At 500V DC.
 Dielectric Withstanding Voltage: 500VAC For 1 Minute.
 Insertion Force: 4.0Kg \pm 2Kg.
 Extraction Force: 4.0Kg \pm 2Kg.

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PPROJECTION

X. \pm
 .X \pm
 .XX \pm
 .XXX \pm
 ANG \pm

照片框

ORDER INFORMATION

PAL-JRL18-75-LF
 SERIES | LEADFREE
 75 OHM
 LONG 18.7mm
 DIP 90°
 JACK

DESCRIPTION: