




Recommended P.C.B Layout

MATERIAL

Insulator : NY6T UL94-V0

Contact Pin : Brass

SPECIFICATION

Current Rate : 1 AMP

Insulation Resistance : 5000MΩMin. at DC 500V

Contact Resistance : 20mΩMax. at DC 100mA

Dielectric Voltage : AC 500V for one minute

Operation Temperature : -40°C to + 105°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ±
.X ± 0.30
.XX ± 0.20
.XXX ±
ANG ± 3°

照片框

ORDER INFORMATION

PAS-V038X20C-2X05-LF
SERIES | | | | LEADFREE
180°SMT | | | | 10 WAY
CAP | | | |
CONTACT 2.0mm
NON POST
HIGH 3.8mm

DESCRIPTION: PIN HEADER 1.27*1.27mm SMT S/T TYPE, S/T TYPE, DUAL ROWS DUAL INSULATORS CAP+T/R