





Electrical Properties

1. 100% Test (Open Short Miss Wire)
2. Contact Resistance: 2Ω Maximum
3. Insulation Resistance: 20MΩ Minimum
4. Hi-Pot: 300V 10ms

6	LABEL	LABEL WX-121 WW/YY	2PCS
5	H.S.T.	HT-TUBE, OD: 0.8mm, L=25mm	1PCS
4	H.S.T.	HT-TUBE, OD: 5.0mm, L=15mm	2PCS
3	TERMINAL	TERMINAL: Copper PA-T-24	3PCS
2	HOUSING	PITCH: 2.0mm 3POS HOUSING, PA-H-03	1PCS
1	CABLE	UL2464 24AWG*3C+A+D, GRAY, OD: 4.5mm, L=675mm	1PCS
ITEM	PARTS NAME	SPECIFICATION STANDARD	Q'TY



P1	Red	Open
1	White	Open
2	Black	Open
3	Drain	Open
NC		
	PIN	OUT

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.35
.XX ± 0.25
.XXX ± 0.15
ANG ±



ORDER INFORMATION

PAX1-030024R1AE-F25N-LF

SERIES

03 WAY

LEADFREE

635mm

FEMALE

AL.FOIL+EARTH WIRE

ROUND CABLE

24 AWG

DESCRIPTION: PH2.0mm 3P to Open(5.0) L=660mm UL2464#24x3C+A+D Gray OD4.5mm