



Ordering Information		
A B	DIM. B = 1.1 mm Voltage 5V	DIM. B = 2.2 mm Voltage 3.3V
A = 5.0mm	PCC-PRL50V5RS-68	PCC-PRL50V3RS-68

MATERIAL:
INSULATOR: PBT UL94V-0 BLACK
CONTACTS: COPPER ALLOY,
GOLD PLATED ON CONTACT AREA,
TIN PLATED ON SOLDER TAIL.
GUIDE/PUSH BUTTON: PBT, UL94V-0/STAINLESS STEEL

ELECTRICAL:
CURRENT RATING: 0.5A AC, DC
TEMPERATURE RANGE: -40°C ~ +85°C
INSULATION RESISTANCE: 1000MΩ MIN.(500V DC)
CONTACT RESISTANCE: 40mΩ MAX.
WITHSTANDING VOLTAGE: 500V AC/MINUTE

TOLERANCES ARE

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE _____

SIZE A4

PPOJECTION 

 $X_{\pm}$ $\chi_{\pm}$ $\cdot XX \pm$
$$.XXX \pm$$

ANG ±

照片框

ORDER INFORMATION

PCC-PRL50VxRS-68-LF

SERIES 68WAY LEADFREE

MALI

DIP 90

LONG RAIL

ANDOFF:5.0ml

11

RIGHT EJECTOR

V3:3.3
V/5:5V

DESCRIPTION: PC68公座單層右短鐵推杆墊高5.0卡槽2.2/1.1 前后2.3魚叉孔 标准支架成品(B TYPE)