



UPPER BOARD	
B=1.1mm 5V	B=2.2mm 3.3V
PCC-PWL00V5-68	PCC-PWL00V3-68

Pin Type	Interface Dim.	Pin No.
Detect	3.50 mm	36, 67
General	4.25 mm	all other pins
Power	5.00 mm	1, 17, 34, 35, 51, 68

MATERIAL :
 INSULATOR : LCP ,UL94V-0
 COLOR : BLACK
 CONTACT : BRASS
 MOUNT EAR : BRASS
 GUIDE/PUSH BUTTON: PBT,UL94V-0
 PLATING :
 CONTACT AREA : GOLD FLASH,5U" GOLD,15U" GOLD
 UNDER PLATING : NICKEL OVERALL
 SOLDER TAIL AREA : TIN
 MOUNT EAR AREA : TIN
 SOLDER TAIL TO BE WITHIN 0.02 UPWARD
 AND DOWNWARD
 FROM Z-DATUM PLACE , AND COMPANARITY
 OF SOLDER TAIL
 TO BE WITHIN 0.10

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
煜倫股份有限公司

DRAWING BY CY
 CHECKED BY GENIUS
 UNIT / mm SCALE 1 : 1
 DATE
 SIZE A4 PPROJECTION

X, ±
 .X ± 0.15
 .XX ± 0.10
 .XXX ± 0.05
 ANG ±

照片框

ORDER INFORMATION

PCC-PWL00Vx-68-LF
 SERIES | | | | LEADFREE
 MALE | | | | 68WAY
 V3:3.3V
 V5:5.0V
 STAND OFF 0.0mm
 LONG RAIL
 90°SMT

DESCRIPTION: PCMCIA 68PIN HEADER WITH GUIDE SMT TYPE

www.morethanall.com