



Note:

- Housing of 26 pin female connector
Insulating Material : PA-9T
Color : black
- Terminals
Plating:
underplate : 30μ"(0.76μm) Nickel
solder tails : 100μ"(2.54μm) Tin
without lead.

Electrical character:

- Insertion loss(IL)
1.7 dB max up to 3.125 GHz;
≤ -5.5 dB up to 6GHz.
- Return loss(RL)
≤ -10 dB up to 3.125 GHz;
≤ -5 dB up to 6GHz.
- Crosstalk(NEXT)
-32 dB max up to 3.125 GHz;
≤ -26 dB at 6GHz.
- Current rating
0.75A per pin minimum.
- Contact Resistance(LLCR)
Initial : 40 mΩ max.
Final(after stress) : 55mΩ max.
- Withstanding voltage
No shorting or other damages
after 500Vrms AC for 1 minute.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

PCE-SW10-26-LF
SERIES | LEADFREE
26 WAY
1.0mm
90°SMT
FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 26 pin female connector for Express card