



## P.C.B Layout

\*Material

Body : 46+30%G.F or PBT+30%G.F,  
UL 94V-0 Rated.Color: Orange 1485C  
CAV.No: A~H  
Contacts : Brass or Phosphor Bronze  
Plating: Gold plating over Nickel on contact  
Area; Tin plating on Solder Tail.

\*Mechanical:

Insertion Force: 1.15N max per contact pair;  
Withdrawal Force: 0.15N min per contact pair;  
Contact Retention Force: 4.9N min per contact;

## \*Electrical Specification

Contact Resistance : 30 Milliohms Max.  
Current Resistance : 1.1 Ampere  
Insulation Resistance : 1000 Megohms Min, At 500V AC.  
Operating Temperature : -55°C to +105°C

**RoHS Compliant**

TOLERANCES ARE

# 照片框

## ORDER INFORMATION

PCIX-DP0R-064-LF

SERIES POST DIP 180°

64 WAY ORANGE LEADFREE

DESCRIPTION: PCI EXPRESS 64Pin Strip Form Pin Plastic Posts (Chip Type)



**[www.morethanall.com](http://www.morethanall.com)**

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE \_\_\_\_\_

SIZE A4

PPOJECTION 

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±