



## NOTES:

### \*Material

Body : Nylon6T UL 94V-0 Rated.

Color: White or Black.

Contacts : Brass or Phosphor Bronze.

Plating: Gold plating over Nickel on contact area;  
Tin Plating On Solder Tail.

CAV.NO.:A~H.

### \*Mechanical:

Insertion Force: 1.15N max per contact pair;

Withdrawal Force: 0.15N min per contact pair;

Contact Retention Force: 4.9N min per contact;

### \*Electrical Specification

Contact Resistance : 30 Milliohms Max.

Current Resistance : 1.1 Ampere

Insulation Resistance : 1000 Megohms Min, At 500V AC.

Operating Temperature : -55°C to +105°C

**RoHS Compliant**

TOLERANCES ARE

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ±  
.X ± 0.38  
.XX ± 0.25  
.XXX ±  
ANG ±

照片框

**ORDER INFORMATION**

PCIX-EN6T-036-LF

SERIES

LEADFREE

36 WAY

NYLON 6T

EDGE CLIP

DESCRIPTION: PCI Express Connector 36 Pin Strip Form Pin Straddle(None Post)

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com