



NOTES

*Material

Body: Nylon6T, UL 94V-0 Rated. Color: White .
 Contacts: Brass.
 Plating: Gold plating over Nickel on contact area;
 Tin Plating On Solder Tail.

*Mechanical:

Insertion Force: 1.15N max per contact pair;
 Withdrawal Force: 0.15N min per contact pair;
 Contact Retention Force: 4.9N min per contact;

*Electrical Specification

Contact Resistance : 30 Milliohms Max.
 Current Resistance : 1.1 Ampere
 Insulation Resistance : 1000 Megohms Min, At 500V AC.
 Operating Temperature : -55°C to +105°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

X.±
 .X±
 .XX±
 .XXX±
 ANG±

照片框

ORDER INFORMATION

PCIX-VP-064-LF
 SERIES | LEADFREE
 64 WAY
 POST
 180°SMT

DESCRIPTION: PCI Express Connector Loose Piece Pin SMT Type 64P (plastic Posts)