



備註 /NOTE

1. 安規 /FAFETY :
  - 1-1. 規格 /RATING : 100V AC MAX OR 12V DC 2A MAX
  - 1-2. 絕緣阻抗 /INSULATION RESISTANCE : 100M MIN AT 500 DC
  - 1-3. 絕緣耐壓 /DIELECTRIC WITHSTANDING VOLTANGE : 1000V AC AT 1 MINUTE
2. 材質 /MATERIAL :
  - 2-1. 鐵殼 /SHELL : 不鏽鋼 /STAINLESS
  - 2-2. 膠芯 /HOUSING : LCP
  - 2-3. 端子 /PIN : 磷銅 /PHOSPHOR BRONZE
3. 電鍍 /PLATING :
  - 3-1. 端子 /PIN : 鍍金 10u" /TIN,GOLD 10u"

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY		X, ± .X ± .XX ± .XXX ± ANG ±
CHECKED BY GENIUS		
UNIT / mm	SCALE 1 : 1	
DATE		
SIZE A4	P PROJECTION	

照片框

ORDER INFORMATION

PCM-JW-15-LF		
SERIES	LEADFREE	
	15WAY	
	90°SMT	
	JACK	

DESCRIPTION: PCMCIA 15P母座