



備註 / NOTE:

1. 安規 / SAFETY:

- 1-1. 規格 / RATING: 100V AC MAX or 12V DC 2A MAX
- 1-2. 絕緣阻抗 / INSULATION RESISTANCE: 50MΩ MIN at 250V DC
- 1-3. 絕緣耐壓 / WITHSTANDING: 250V AC at 1 MINUTE

2. 材質 / MATERIAL:

- 2-1. 膠芯 / HOUSING: LCP (黑色 / BLACK)
- 2-2. 針 / PIN: 磷銅 / PHOSPHOR BRONZE
- 2-3. 彈片 / SPRING: 不鏽鋼 SUS#301 / STAINLESS SUS#301
- 2-4. 外套 / PLASTIC COVER: PC(防火)94-V0
- 2-5. 上蓋 / METAL UP COVER: 洋白板 / NICKEL SILVER
- 2-6. 下蓋 / METAL DOWN COVER: 黃銅 / BRASS

3. 電鍍 / PLATING:

- 3-1. 針 / PIN: 錫, 金 / TIN, GOLD
- 3-2. 下蓋 / METAL DOWN COVER: SEE TABLE B

4. 外觀 / SURFACE:

- 4-1. 不可缺針
- 4-2. 不可壓傷變形
- 4-3. 不可刮傷露銅
- 4-4. 不可有射出缺料或縮水現象
- 4-5. 內孔不可阻塞
- 4-6. 不可彎曲變形
- 4-7. 毛邊不可過大
- 4-8. 刮痕不可明顯

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION

照片框

ORDER INFORMATION

PCM-PA-15-LF
SERIES | LEADFREE
15 WAY
ASSEMBLY
MALE

DESCRIPTION: PCMCIA 15P

www.morethanall.com