



備註 /NOTE:

1. 安規 /SAFETY:
  - 1-1. 規格 /RATING: 100V AC MAX or 12V DC 2A MAX
  - 1-2. 絕緣阻抗 /INSULATION RESISTANCE: 50M ohm MIN at 250V DC
  - 1-3. 絕緣耐壓 /DIELECTRIC WITHSTANDING VOLTAGE: 250V AC at 1 MIN
2. 材質 /MATERIAL:
  - 2-1. 膠芯 /HOUSING: NYLON 46, BLACK, GF UL94-V0
  - 2-2. 固定座 /INSERT: P.B.T.+30%GF, BLACK, GF UL94-V0
  - 2-3. 端子 /CONTACT:PHOSPHOR BRONZE
  - 2-4. 上蓋 /METAL TOP SHELL: 不鏽鋼 /STAINLESS STEEL
  - 2-5. 下蓋 /METAL BOTT SHELL: 不鏽鋼 /STAINLESS STEEL
  - 2-6. 外套 NYLON 66, (15% G/F), GF UL94-V0, BLACK

3. 電鍍 /PLATING:

端子 /CONTACT:  
 UNDER-PLATE 50u" MIN NICKEL ALL OVER,  
 PLATE 150u" MIN TIN/LEAD IN TAIL ZONE,  
 PLATE 5u" MIN GOLD OVER 30u" MIN Pd/Ni  
 IN CONTACT AREA.



RoHS Compliant

TOLERANCES ARE

X. ±  
 .X ± 0.20  
 .XX ± 0.10  
 .XXX ± 0.05  
 ANG ± 1°

DRAWING BY CY	
CHECKED BY GENIUS	
UNIT / mm	SCALE 1 : 1
DATE	
SIZE A4	PJECTION

ORDER INFORMATION

PCM-PA-15A23-LF  
 SERIES | LEADFREE  
 | A23 KEYWAY  
 | 15 WAY  
 | ASSEMBLY  
 | MALE

DESCRIPTION: PCMCIA 15P 母座 (HD) -A23 (SR MOLDING) 成品

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES  
 煜倫股份有限公司  
 www.morethanall.com