



備註/NOTE :

1. 安規 / SAFETY :

- 1-1. 規格 / RATING : 100V AC MAX or 12V DC 2A MAX
- 1-2. 絕緣阻抗 / INSULATION RESISTANCE : 200MΩ MIN at 250V DC
- 1-3. 絕緣耐壓 / WITHSTANDING : 250V AC at 1 MINUTE
- 1-4. 接觸阻抗 / CONTACT RESISTANCE : 50mΩ MAX AT DC 1A

2. 材質 / MATERIAL :

- 2-1. 膠芯 / HOUSING : NYLON GF33% UL94-V0
- 2-2. 針 / PIN : 磷銅 / PHOSPHOR BRONZE
- 2-3. 上線夾 / PLASTIC UP COVER : PBT 30% GF-94V0

- 2-4. 下線夾 / PLASTIC DOWN COVERN : PBT 30% GF-94V0
- 2-5. 外套 / PLASTIC COVER : P.P UL 94-V0
- 2-6. 上蓋 / METAL UP COVER : 不鏽鋼
- 2-7. 下蓋 / METAL DOWN COVER : 不鏽鋼 / STAINLESS
- 2-8. 線夾 / CABLE FIXED : 不鏽鋼 / STAINLESS

3. 電鍍 / PLATING :

- 3-1. 針 / PIN: CONTACT AREA : GOLD 5u"
SOLDER ARES : TIN-LEAD 100u"MIN

RoHS Compliant



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

TOLERANCES ARE

- X. ±
- .X ±
- .XX ±
- .XXX ±
- ANG ±



ORDER INFORMATION

PCM-PA-32-LF
 SERIES | LEADFREE
 | 32WAY
 | ASSEMBLY
 MALE

DESCRIPTION: PCMCIA 32PIN 公座成品