



CONTACT

INNER:6 FINGER CONTACT, IN HEAT TREATED BERYLLIUM COPPER

FINISH: GOLD OVER 2-3 μ NICKEL OVER

COPPER FLASH

OUTER SLEEVE

FINISH: 5 μ TIN OVER 2-3 μ INCKEL OVER COPPER FLASH

INSULATOR

GLASS FILLED POLYPHENLENE SULFIDE
UL94V-0 RATED. (P.P.S.)

ELECTRICAL DATA

CONTACT RESISTANCE < 4 ml PER CONTACT

INSULATION RESISTANCE > 10¹¹ QU-100V

WORKING VOLTAGE: 10mv-60V

MECHANICAL DATA

TEMPERATURE RANGE: -55°C TO +155°C

MECHANICAL LIFE CYCLE:

1000 CYCLE INSERTIONS AND WITHDRAWALS
WITH STEEL PIN 0.46mm

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±

.X ±

.XX ±

.XXX ±

ANG ±

照片框

ORDER INFORMATION

PGA-D-145-LF
SERIES | LEADFREE
145 WAY
DIP 180°

煜倫股份有限公司

www.morethanall.com

PPOJECTION

DESCRIPTION: PGA SOCKET 145P