



MATERIAL & FINISH

- * Contact: Beryllium Copper (BeCu)
- * Sleeve: Brass
 - Plating: G=Gold Plated
 - T=Tin Plated
- * Insulator: Thermoplastic polyester
- * Resist to Soldering Heat: Max. 260°C, 5 Sec.
- * Solderability: 235°C, 5 Sec.
- * Current Rating: 3A
- * Voltage rated: 100VRMS / 150VDC
- * Contact Resistance : 10 Milliohm
- * Insulator Resistance : 10000M ohm min.
- * Dielectric Strength : 1000 VRMS Min
- * Rated Voltage : 100 VRMS / 150VDC
- * Temperature: - 55°C TO + 125°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY
CHECKED BY GENIUS
UNIT / mm SCALE 1 : 1
DATE

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

PGA-D-299-LF
SERIES | LEADFREE
299 WAY
DIP 180°

煜倫股份有限公司

www.morethanall.com

SIZE A4

PPOJECTION

DESCRIPTION: PGA STOCKER 299P