



Note:

.Materials

Plunger & Barrel : Brass

Spring : Stainless Steel

.Plating

Contact Surface : 10μ " minimum Au over,
 50μ " ~ 100μ " minimum Ni

.Electrical

Contact Resistance : $50m \Omega$ max
at Working Length(Quiescence)

Current Rating: DC 12V , 1A

.Mechanical

Total Length : 10.70 mm

Working Length : 9.70 mm

Spring Force : $150 \text{ g} \pm 20\%$ at Working Length

Durability : 10,000 Cycles minimum

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, \pm
.X ± 0.20
.XX ± 0.10
.XXX ± 0.05
ANG \pm

PJECTION

照片框

ORDER INFORMATION

PGP-S-075132115-LF
SERIES | | | LEADFREE
| | | MAX WORKING HEIGHT 11.5mm
| | | TOTAL LONG 13.2mm
| | | 0.75 ϕ
SOLDER

DESCRIPTION: