



1.材料電鍍：

1-1針筒為黃銅合金,鍍鎳50-60 μ "鍍金1.5 μ "

1-2針頭為黃銅合金,鍍鎳50-60 μ "鍍金1.5 μ "

2.持續工作電流：1.0A,彈簧使用壽命20000次以上

3.工作電壓：低於12V@25 $^{\circ}$ C

4.鹽霧試驗：5%鹽溶液24小時無鏽蝕

5.可焊性試驗：230 \pm 5 $^{\circ}$ C 1second濕焊覆蓋率95%以上

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X. \pm 0.50

.X \pm 0.15

.XX \pm 0.10

.XXX \pm

ANG \pm

PPOJECTION

照片框

ORDER INFORMATION

PGP-V-094025-LF

SERIES | LEADFREE
2.5mm WORKING HIGH
4.0mm TOTAL HIGH
0.9mm DIA
180 $^{\circ}$ SMT

DESCRIPTION: Pogo Pin