



1. MATERIAL :
 - 1-1. SPRING : PHOSPHOR BRONZE
 - 1-2. BARREL : BRASS
 - 1-3. PLUNGER : BRASS
2. FINISH :
 - 1-1. SPRING : GOLD FLASH MICRO INCHES MIN.
 - 1-2. BARREL : 10 MICRO INCHES MIN. GOLD PLATED
 - 1-3. PLUNGER : 15 MICRO INCHES MIN. GOLD PLATED
3. Mechanical Characteristics:
 - 3-1. Full Stroke : 1.0 mm
 - 3-2. Spring Force : $0.6n \pm 0.2n$ at Working Length
 - 3-2. Mechanical Life : 10,000 cycle
4. Electrical Characteristics:
 - 4-1. Current Rating : 12 VCD , 3A
 - 4-2. Contact Resistance : $50 \text{ m} \Omega$ Max

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X, \pm
.X \pm 0.10
.XX \pm 0.05
.XXX \pm 0.03
ANG \pm

PJECTION

照片框

ORDER INFORMATION

PGP-V-104030-LF
SERIES | | | LEADFREE
| | | 3.0mm WORKING HIGH
| | | 4.0mm TOTAL HIGH
| | | 1.0mm DIA
| | | 180°SMT

DESCRIPTION: