



NOTE:

1. MATERIAL
 HOUSING: PA 9T, COLOR: BLACK
 PLUNGER: BRASS, 5u" GOLD PLATING 50u" MIN. NICKEL UNDERPLATEE.
 BARREL: BRASS, (c3604) 5u" GOLD PLATING OVER 50u" MIN. NICKEL UNDERPLATED
 SPRING: SUS304
2. SPECIFICATION:
 ELECTRICAL.
 CURRENT RATING: 12VDC, 1A
 CONTACT RESISTANCE : 50mΩ Max.
 ENVIRONMENTAL:
 TEMPERATURE RANGE: -40~85°C
3. MECHANICAL FUNCTION:
 SPRING PROBE FORCE:
 WORKING STROKE (SINGLE PIN): 100±20gf AT 1.5mm RECOMMEND STROE
 MAX. STROKE: 1.8mm FULL STROKE.
 DURABILITY: 100,000 CYCLES/1.50mm STROKE

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
 X ± 0.25
 .XX ± 0.20
 .XXX ± 0.02
 ANG ±

PJECTION

照片框

ORDER INFORMATION

PGP26-D130E-1X07-LF

SERIES | | | LEADFREE
 | | | 07 WAY
 | | | EAR
 | | | HIGH 13.0mm
 | | | DIP 180°

DESCRIPTION: 7PIN(2.55PH)(电镀金 10U"鍍50~100u")