



RECOMMENDE PCB LAYOUT

Note:

.Materials

Housing : Thermoplastic UL 94V-0. Black

Plunger & Barrel : Copper Alloy

Spring : Stainless Steel

.Plating

Contact Surface : 10 μ" Au Plated on Contact Area,  
10 μ" Au Plated on Solder Tails,  
60 μ" Ni Under-Plated

.Electrical

Contact Resistance : 50m Ω max  
at Working Length

.Mechanical

Total Length : 6.50 mm

Working Length : 5.10mm

Spring Force : 140g ± 20% at Working Length

Durability : 10,000 Cycles minimum

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

照片框

ORDER INFORMATION

PGP26-V65X-1X03-LF

SERIES | | | LEADFREE  
| | | 03 WAY  
| | | NON POST  
| | | HIGH 6.5mm  
| | | 180°SMT

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 3PIN PO GO PIN CONN