



RECOMMENDE PCB LAYOUT

Note:

.Materials

Housing : Thermoplastic UL 94V-0. Black
 Plunger & Barrel : Copper Alloy
 Spring : Stainless Steel

.Plating

Contact Surface : 10 μ" Au Plated on Contact Area,
 10 μ" Au Plated on Solder Tails,
 60 μ" Ni Under-Plated

.Electrical

Contact Resistance : 50mΩ max
 at Working Length

.Mechanical

Total Length : 6.50 mm
 Working Length : 5.10mm
 Spring Force : 140g ± 20% at Working Length
 Durability : 10,000 Cycles minimum

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

PGP26-V65X-1X13-LF

SERIES

||

||

||

||

||

||

||

||

||

||

||

||

||

||

||

||

||

LEADFREE
 13 WAY
 NON POST
 HIGH 6.5mm
 180°SMT

DESCRIPTION: