

## SPECIFICATIONS

### Electrical

Current Rating: 2A AC, DC

Voltage Rating: 100V AC/ max.

Operating Temp.: -25°C ~ +85°C

Insulation Resistance: 1000MΩ/ min.

Dielectric Withstanding Voltage: 800V AC/ min.

Contact Resistance: 20mΩ/ max.

### Material

Material: Nylon 66, UL94V-0

Poles	Dimension mm (in.)		Part No.	Note.
	A	B		
2	2.0(0.079)	5.8(0.228)	PH-H-02	
3	4.0(0.157)	7.8(0.307)	PH-H-03	
4	6.0(0.236)	9.8(0.386)	PH-H-04	
5	8.0(0.315)	11.8(0.465)	PH-H-05	
6	10.0(0.394)	13.8(0.543)	PH-H-06	
7	12.0(0.472)	15.8(0.622)	PH-H-07	
8	14.0(0.551)	17.8(0.701)	PH-H-08	
9	16.0(0.630)	19.8(0.780)	PH-H-09	
10	18.0(0.709)	21.8(0.858)	PH-H-10	
11	20.0(0.787)	23.8(0.937)	PH-H-11	
12	22.0(0.886)	25.8(1.016)	PH-H-12	
13	24.0(0.945)	27.8(1.094)	PH-H-13	
14	26.0(1.024)	29.8(1.173)	PH-H-14	
15	28.0(1.102)	31.8(1.252)	PH-H-15	
16	30.0(1.181)	33.8(1.331)	PH-H-16	

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/ mm


SCALE 1:1

DATE

SIZE A4

X, ±  
.X ± 0.30  
.XX ± 0.20  
.XXX ±  
ANG ±

PPOJECTION



### ORDER INFORMATION

PH-H-xx-LF  
SERIES | LEADFREE  
02~16WAY  
HOUSING

DESCRIPTION: 2.0mm Wire-to-Board Housing