



P.C.B Hole Layout

Specifications

- 1.Current Rating : 2.0A AC,DC
- 2.Voltage rating : 250V AC,DC
- 3.Temperature range : -25°C ~ +85°C
- 4.Contact resistance : 20mΩ Max
- 5.Insulation resistance : 100MΩ Min
- 6.Withstanding voltage : 200 V AC/minute

	A	B	C
2P	8.0	4.8	2.0
3P	10.0	6.8	4.0
4P	12.0	8.8	6.0
5P	14.0	10.8	8.0
6P	16.0	12.8	10.0
7P	18.0	14.8	12.0
8P	20.0	16.8	14.0
9P	22.0	18.8	16.0
10P	24.0	20.8	18.0
11P	26.0	22.8	20.0
12P	28.0	24.8	22.0
13P	30.0	26.8	24.0
14P	32.0	28.8	26.0
15P	34.0	30.8	28.0
16P	36.0	32.8	30.0

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

照片框

ORDER INFORMATION

PH-W-xx-LF
SERIES | LEADFREE
02~16WAY
90°SMT

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: WAFER 2.0 SMT 90度