



Specification

- 1.Current Rating:2A
- 2.Voltage Rating:100V AC/DC
- 3.Contact Resistance:20mΩ Max.
- 4.Insulation Resistance:1000MΩ Min.
- 5.Dielectric Withstanding Voltage:AC800V/Minute
- 6.Operating Temperature:-25℃~85℃

Material:

- 1.Housing:High Temperature Thermoplastic UL94V-0
- 2.Tab:Copper Alloy
- 3.Contact Pin:Copper Alloy SQ. Pin 0.50mm

Finish:

- 1.Housing: HTN UL94V-0 Natural None H.F.
- 2.Contact PIN: Gold Flash Over Nickel

PIN	DIM.A	DIM.B	DIM.C	PIN	DIM.A	DIM.B	DIM.C
02	2.00	4.80	8.00	10	18.00	20.80	24.00
03	4.00	6.80	10.00	11	20.00	22.80	26.00
04	6.00	8.80	12.00	12	22.00	24.80	28.00
05	8.00	10.80	14.00	13	24.00	26.80	30.00
06	10.00	12.80	16.00	14	26.00	28.80	32.00
07	12.00	14.80	18.00	15	28.00	30.80	34.00
08	14.00	16.80	20.00	16	30.00	32.80	36.00
09	16.00	18.80	22.00				

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
X, ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

PH-WG-xx-LF
SERIES | LEADFREE
| 02~16 WAY
| GOLD
| 90°SMT

DESCRIPTION: