

P1.
PH-H-05

P2.
PH-H-05

WIRING DIAGRAM

P1		P2	
BROWN 1	—————	1 BROWN	
BROWN 2	—————	2 BROWN	
BROWN 3	—————	3 BROWN	
BLACK 4	—————	4 BLACK	
RED 5	—————	5 RED	

NO.	PART NO.	Q'TY	UNITS	DESCRIPTION
3	TERMINAL	10	PCS	PH-T-26
2	HOUSING	2	PCS	PH-H-05
1	CABLE	600	mm	UL1007 24&26&28 AWG*5C

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X. ±


.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION



ORDER INFORMATION

PHX2-05xxyy-Fxxx-LF

SERIES

LEADFREE

24C:240mm

0505:05 TO 05 WAY

0504:05 TO 04 WAY

:

FEMALE TO FEMALE

24:24 AWG

26:26 AWG

28:28 AWG

DESCRIPTION: JST2.0-5PH/JST2.0-5PH/600mmBLACK