



T:1.6 Dimensions of PC board holes

Tolerance : ±0.05(Printed-top view)  
SS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

5	HOUSING	1	PBT		UL-94V0(BLACK)
4	CURVE PIECE	1	C2680	t=0.30	Ni(30u") /Ag(10u") PLATED
3	3# SPRING PIECE	1	C5191	t=0.20	Ni(30u") /Ag(10u") PLATED
2	2# SPRING PIECE	1	C5191	t=0.25	Ni(30u") /Ag(10u") PLATED
1	1# SPRING PIECE	1	C5191	t=0.20	Ni(30u") /Ag(10u") PLATED
LTR	PART NAME	QTY	MATERIAL		REMARK

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X.±

.X±

.XX±

.XXX±

ANG±

PJECTION

照片框

ORDER INFORMATION

PJ-R26M-04C-LF

SERIES | LEADFREE  
4P3C  
METAL  
POST 2.5+6.0  
DIP 90°

DESCRIPTION: MINIATURE JACK