



NO.	NAME	MATERIAL	FINISH	Q'TY
1	GROUND TERM.	C.R.S. 0.4THK	TIN PLATED	1
2	TIP TERM.	PHOS. BRONZE 0.25THK	TIN PLATED	1
3	RING TERM.	BRASS 0.5THK	TIN PLATED	1
4	BUSHING	BRASS	NICKEL PLATED	1
5	HOUSING	PBT G.F.	BLACK	1

Specification:

Contact Resistance: 30m Ohm. Max. At AC 100mA Max.1KHz

Insulation Resistance: 100M Ohm Min. At 500V DC.

Rated Voltage And Current: DC 12V,2A Max ; AC 100V,1A Max.

Dielectric Withstanding Voltage: 500V AC For 1 Minute.

Durability (Life Test):

A: For Phosphor Bronze 1500 Cycles Minimum.

B: For PBS 2000 Cycles Minimum.

Insertion Force: 0.3~3.0 Kg.

Extraction Force: 0.3~3.0Kg.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION

照片框

ORDER INFORMATION

PJ-R33T5-03B-LF
SERIES | LEADFREE
3P2C
THREAD 5.0mm
3.5+3.5mm
DIP 90°

DESCRIPTION: 3.5mm EARPHONEJACK 3 PIN

煜倫股份有限公司

www.morethanall.com