


T:1.6 Dimensions of PC board holes
Tolerance : ±0.05(Printed-top view)



9	MYLAR	1	POLYIMIDE TAPE	
8	HOUSING	1	PA9T(GN2330)	UL-94V0(BLACK)
7	8# CONTACT FOOT	1	C5191 t=0.25	MBNi(20u*min) Ag(8u*min) PLATED
6	7# CURVE PIECE	1	C5191 t=0.20	MBNi(20u*min) Ag(8u*min) PLATED
5	6# CURVE PIECE	1	C5191 t=0.20	MBNi(20u*min) Ag(8u*min) PLATED
4	4# CURVE PIECE	1	C5191 t=0.20	MBNi(20u*min) Ag(8u*min) PLATED
3	3# CONTACT FOOT	1	C5191 t=0.25	MBNi(20u*min) Ag(8u*min) PLATED
2	2# CONTACT FOOT	1	C5191 t=0.25	MBNi(20u*min) Ag(8u*min) PLATED
1	1# CONTACT FOOT	1	C5191 t=0.25	MBNi(20u*min) Ag(8u*min) PLATED
LTR	PART NAME	QTY	MATERIAL	REMARK

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.2

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1 : 1


.XXX±

DATE

ANG±

SIZE A4

PJECTION



ORDER INFORMATION

PJ-W27B1C-07D2-LF

SERIES | MYLAR | BUSHING 1.2mm | POST 2.3+7.0mm | 90°SMT | LEADFREE | 7P4C2

DESCRIPTION: MINIATURE JACK

煜倫股份有限公司

www.morethanall.com