



RECOMMENDED P.C.B HOLE LAYOUT
DEFAULT TOLERANCE: ±0.05

PORT	A	B	C	D	E	F
COLOUR	BLUE	GREEN	RED	BLUE	GREEN	RED

- MATERIALS**
- HOUSING : THERMOPLASTIC, UL 94V-0(E107536)
 - TERMINAL : COPPER ALLOY, SELESTIVE
1u" MIN. GOLD PLATING AT INTERFACE SIDE,
120u" MIN. TIN PLATING AT SOLDER SIDE,
50u" MIN. NICKEL UNDERPLATING OVERALL.
 - FRONT SHIELD : BRASS 100u" MIN. TIN PLATING OVERALL
 - BACK SHIELD : BRASS 100u" MIN. NICKEL PLATING OVERALL

- SPECIFICATION**
- CURRENT RATING : 0.3 AMP. MAX.
 - DIELECTRIC WITHSTANDING VOLTAGE :
500V AC R.M.S. FOR PER MINUTE.
 - INSULATION RESISTANCE : 100M OHMS MIN. AT 500V DC.
 - CONTACT RESISTANCE : 50m OHMS MAX.
 - OPERATING TEMPERATURE : -25°C ~ +85°C.
 - DURABILITY : 5000 CYCLES.
 - MATING FORCE : 5kgs MAX.
 - UNMATING FORCE : 0.4~3.0kgs
 - MAX PROCESSING TEMPERATURE :
230°C FOR 30-60 SECONDS. (HI-TEMP. PLASTIC)



PART NO. PJC2-RF35-05D

DWG NO. PJC2-RF35-05D

CHECKED BY CY

TOLERANCES ARE

DESCRIPTION: SMART AUDIO JACK
六合一 PITCH 11.0mm

焯倫有限公司

FILE NO.

DRAWING BY

.X ± 0.3
.XX ± 0.15
.XXX ±
AWG

AREA	REVISIONS	HK	DATE
------	-----------	----	------

UNIT / mm SCALE 1:1

PROJECTION