

MATERIAL:

INSULATOR :Hi-temp PBT UL 94V-0
 Contact material:phosphor bronze JIS 5210
 Contact Platred :120 μ "tin over 30 μ "nickel

SPECIFICATIONS:

Temperature range:-50°C to 105°C
 CURRENT Rating :1 AMP
 Capacitance:1.0 Picoforads (Max)
 Contact resistance:30 Milliohms (Max)
 Insulation Resistance :1000 Megohms (Min)
 Withstanding Voltage: AC 600 Vrms

MIDDLE TYPE:

NO OF CONTACT	A \pm 0.15	B \pm 0.15	C \pm 0.1	D \pm 0.1	E \pm 0.1	F \pm 0.1
20 PBT	15.50	15.50	5.08	5.08	5.08	5.08
28 PBT	18.04	18.04	7.62	7.62	7.62	7.62
32 PBT	18.04	20.60	7.62	10.16	7.62	10.16
44 PBT	23.48	23.48	12.70	12.70	12.70	12.70
52 PBT	25.88	25.88	15.24	15.24	15.24	15.24
68 PBT	31.04	31.04	20.32	20.32	20.32	20.32
84 PBT	36.04	36.04	25.40	25.40	25.40	25.40
68 PBT	31.66	31.66	20.32	20.32	20.32	20.32
84 PBT	36.66	36.66	25.40	25.40	25.40	25.40

THIN TYPE:

NO OF CONTACT	A \pm 0.15	B \pm 0.15	C \pm 0.1	D \pm 0.1	E \pm 0.1	F \pm 0.1
44	23.48	23.48	12.70	12.70	12.70	12.70
68	31.04	31.04	20.32	20.32	20.32	20.32
84	36.04	36.04	25.40	25.40	25.40	25.40

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm

SCALE 1:1

DATE


SIZE A4

PJECTION

X, \pm
 X \pm 0.25
 .XX \pm 0.15
 .XXX \pm 0.06
 ANG \pm 1°



ORDER INFORMATION



DESCRIPTION: PLCC SOCKET DIP