



RECOMMENDED P.C.B LAYOUT

MATERIAL

- * Insulator: PPS
- * Contact: Phosphor Bronze
- * Plating: Tin Plating over Nickel

SPECIFICATION

- * Rating Current : 1.0A , AC
- * Contact Resistance : $20\text{m}\Omega$ Max
- * Insulator Resistance : $1000\text{M}\Omega$ Min
- * Dielectric Withstanding :
600 VAC(RMS), 60Hz , one minute Hold
- * Temperature Range : $-55^{\circ}\text{C} \sim +125^{\circ}\text{C}$

PART NO.	PIN	DIM A	DIM B	DIM C	DIM D	DIM E	DIM F	DIM G	DIM I	DIM J	DIM H
PL-VP-20	20	5.08	15.24	16.70	5.08	15.24	8.48	8.48	9.40	9.40	12.70
PL-VP-28	28	7.62	17.78	20.30	7.62	17.78	11.02	11.02	11.94	11.94	15.24
PL-VP-32	32	7.62	17.78	22.50	10.16	20.32	11.02	13.56	11.94	14.48	17.78
PL-VP-44	44	12.70	22.86	27.50	12.70	22.86	16.10	16.10	17.02	17.02	20.32
PL-VP-52	52	15.24	25.40	31.10	15.24	25.40	18.64	18.64	19.56	19.56	22.86
PL-VP-68	68	20.32	30.86	38.30	20.32	30.86	23.72	23.72	24.64	24.64	27.94
PL-VP-84	84	25.40	35.94	45.50	25.40	35.94	28.80	28.80	29.72	29.72	33.02

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

PL-VP-xx-LF
SERIES | LEADFREE
20~84WAY
POST
180°SMT

DESCRIPTION: PLCC Socket Surface Mount Type Pitch 1.27 mm