



SPECIFICATIONS:
 Current Rating:PIN Number-A 10A;PIN Number-B 5A
 Operating Voltage:400V MAX.
 Dielectric Withstanding Voltage:2500V MAX.
 Contact Resistance:5.0mΩ MAX.
 Cable OD:Ø3.0-Ø8.5mm
 Waterproof Standard:IP 67

PIN NUMBER-A(10A)				PIN NUMBER-B(5A)		
2P	3P	4P	5P	7P	8P	9P

3	Metal	Zinc Alloy	Chrome Ptd.	1
2	Contact	Brass	Gold Ptd.	2-9
1	Housing	PBT		5
No.	Description	Material	Treat	Q'ty

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X.±
 .X±
 .XX±
 .XXX±
 ANG±

PJECTION

照片框

ORDER INFORMATION

PLM23-PA-xx-LF
 SERIES T LEADFREE
 02-09 WAY
 ASSEMBLY
 MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: