



ALL DIMENSION IN MM UNLESS OTHERWISE STATED : 0.= ±0.1mm 00.= ±0.2mm

Housing Material : Polyamide 66 (PA66), grey and white flame-retardant to UL 94V-2

Current : 30A (cULus), 24A (VDE)

Voltage : 600V (cULus), 450V (VDE)

Working Temp : 100° C

Wire Range : Installation side: 0.75 ~ 2.5mm² sol, #18-#16 AWG, Sol

Lighting side: 0.5 ~ 2.5mm² sol/Str, #18-#16 AWG, Sol/Str Cu

Stripping Length : 9 ~ 11mm (0.35 ~ 0.43inch)

International Approvals

cULus, CE, VDE, FIMKO, KEMA, CEBEC

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PJECTION

照片框

ORDER INFORMATION

PNC-Wcc-01-LF
SERIES | LEADFREE
01WAY
GY:GRAY
WH:WHITE
WIRE TO WIRE

DESCRIPTION: