



ALL DIMENSION IN MM UNLESS OTHERWISE STATED : 0.= ±0.1mm 00.= ±0.2mm

**Housing Material :** Polyamide 66 (PA66), grey and white flame-retardant to UL 94V-2

**Current :** 30A (cULus), 24A (VDE)

**Voltage :** 600V (cULus), 450V (VDE)

**Working Temp :** 100° C

**Wire Range :** Installation side: 0.75 ~ 2.5mm<sup>2</sup>, sol.

Lighting side: 0.5 ~ 2.5mm<sup>2</sup>, sol/Str.

**Stripping Length :** 9 ~ 11mm (0.35 ~ 0.43inch)

**International Approvals**

cULus, CE, VDE, FIMKO, KEMA, CEBEC

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PJECTION

照片框

**ORDER INFORMATION**

PNC-Wcc-02-LF  
SERIES | LEADFREE  
02WAY  
GY:GRAY  
WH:WHITE  
WIRE TO WIRE

DESCRIPTION: