

PCB LAYOUT

FEATURES

- *TTL INTERFACE COMPATIBLE
- *HIGH SPEED OPTIC SIGNAL TRANSMISSION
- *BUILT-IN LED DRIVER
- *LOW POWER CONSUMPTION
- *Pin Function: 1.GND
2.Vcc
3.Vin

ABSOLUTE MAXIMUM RATINGS AT TA=25°C		
PARAMETER	MAXIMUM RATING	UNIT
Supply Voltage(Vcc)	-0.5~+7	V
Input Voltage (V _{IN})	-0.5~Vcc+0.5	V
Power Dissipation (P)	120	mW
Operating Temperature Range	-20°C to +70°C	
Storage Temperature Rang	-40°C to +70°C	
Lead Soldering Temperature 1.6mm (.063") From Body	260°C for 10 Seconds	

POF-T0P-03-LF
LEADFREE
RoHS Compliant



PART NO. POF-T0P-03

DWG NO. POF-T0P-03

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2

.XX ± 0.15

.XXX ±

AWG

DESCRIPTION:

Fiber Optic Transmitter Connector

AREA

REVISIONS

HK

DATE

焯倫股份有限公司