

NOTES:

***Material**

Housing&CAP: LCP, UL 94V-0 rated, Color: Black;
Contact: Brass;
Plating: Au plating on contact area;
Sn(100u" min.) plating on solder tail;
Ni (50u" min.) underplating overall.
Harpoon: Brass;
Plating: Sn plating(100u" min.) over Ni(50u" min.).

***Mechanical**

Insertion Force: 59N max.
Withdrawal Force: 6N min.
Durability: 500 cycles

***Electrical Specification**

Current Rating: 1.5 Ampere per power contact;
Contact Resistance: 30 mΩ max.
Insulation Resistance: 1000 MΩ min.
Dielectric Withstanding Voltage: 500 VAC.

***Environmental**

Operating Temperature: 0°C to +55°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ± 0.35

UNIT / mm

SCALE 1 : 1

.XX ± 0.25


DATE

.XXX ± 0.15

ANG ± 3°

SIZE A4

PJECTION



ORDER INFORMATION

PSAS-PWBFMP2C-68-LF

SERIES | | | | LEADFREE

CAP | | | | 68 WAY

MALE | | | | METAL FOOT+ POST x2

90°SMT | | | | OFFSET | | | | BOTTOM CONTACT

DESCRIPTION: SAS/PCIe 68P SMT (Reverse Subside Type (0.55) Male

煜倫股份有限公司

www.morethanall.com