


TOLERANCES ±0.38 UNLESS OTHERWISE SPECIFIED
ANGULAR ±2°

Rating	2.5A 250VAC,5A 125VAC,250VAC-1/4HP		
	 2.5A GP 250VAC,5A GP 125VAC T65		
Contact Resistance	50mΩ Max		
Insulation Resistance	DC 500V 100M OHM MIN.		
Dielectric Strength	AC 1500V 1 minute		

Descriptions:

1. Housing : PA#66 (UL flame: 94V-0)
2. Button : PA#66 (UL flame: 94V-0)
3. Mid-Body: PA#66 (UL flame: 94V-0)
4. Axial : PA#66 (UL flame: 94V-0)
5. Plate Cover: PA#66 (UL flame: 94V-0)
6. Terminal: C5210-H
7. Contact Plate: C5210-H



NOTE:

1. ELECTRICAL RATING:
2.5A 250VAC 50,000cycles 0° to 65°C UNDER DEMKO AND ENEC APPROVED.
2. PLUNGER FORCE WHEN DEPRESSED 8 OZ.(227 GRAM) MAX.
3. SCI MARK & WEEKLY DATECODE VOLTAGE & RATING MUST BE CLEARLY PRINTED ON PARTS.

PACKAGE:

1. 50 PCS/POLYBAG
2. 20PCS POLYBAGS(1,000 PCS)/CARTON

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XXX ±

DATE

ANG ±

SIZE A4

PPOJECTION

照片框

ORDER INFORMATION

PSW2529-RPA-02-LF

SERIES

LEADFREE

02 WAY

PANEL FRONT

DIP 90°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: