



**NOTES**

- \* Poles:2-10
- \* Material:NORYL UL94V-1 BLACK

**Specifications**

- \* Current rating: 3A AC, DC
- \* Voltage rating: 250V AC, DC
- \* Temperature range: -25°C~+85°C
- \* Insulation resistance: 1,000MΩ min.
- \* Withstand voltage: 800V AC/minute

CIRCUITS	DIMENSION in.(mm)	
	A	B
2	0.100(2.54)	0.208(5.28)
3	0.200(5.08)	0.308(7.82)
4	0.300(7.62)	0.408(10.36)
5	0.400(10.16)	0.508(12.90)
6	0.500(12.70)	0.608(15.44)
7	0.600(15.24)	0.708(17.98)
8	0.700(17.78)	0.808(20.52)
9	0.800(20.32)	0.908(23.06)
10	0.900(22.86)	1.008(25.60)

**RoHS Compliant**

TOLERANCES ARE



**煜倫股份有限公司**

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PJECTION

照片框

**ORDER INFORMATION**

PVK-H-1Xxx-LF  
SERIES | LEADFREE  
1X02:02WAY  
1X10:10WAY  
HOUSING

DESCRIPTION: