



WIRING DIAGRAM

P1		P2
1	RED	1
2	WHITE	2
3	GREEN	3
4	BLACK	4

ELECTRICAL SPECIFICATION:

- 1.100% OPEN SHORT&MISS WIRE TEST
- 2.VOLTAGE:DC 300V
- 3.INSULATOR RESISTANCE:2M OHM MIN
- 4.CONDUCTIVE RESISTANCE:5 OHM MAX

No.	NAME	DESCRIPTION	Q' TY
1	CONNECTOR	USB 2.0 A FEMALE WITH METAL BOOT, NICKEL PLATED;WHITE INSULATION	1PC
2	CABLE	UL 2464 26WG*4C OD:3.5MM BLACK JACKET L=150MM	1PC
3	HOUSING	DUPONT 2.54 4P*1R HOUSING BLACK OR EQUIVALENT	1PC
4	TERMINAL	DUPONT 2.54 TERMINAL TIN-PLATED OR EQUIVALENT	4PCS

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION

照片框

ORDER INFORMATION

PVUB-044A2V26-F15C-LF

SERIES

LEADFREE

150mm

FEMALE TO FEMALE

26 AWG

2.0 REV

4 PIN TO 4 PIN A TYPE

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com